



ARDEX WPM 265

(Sheltercoat Water Based Primer)

Creates a positive bond between the substrate and most water based coatings

Can be used on substrates like new and old concrete, timber and compressed fibre boards

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX WPM 265

(Sheltercoat Water Based Primer)

DESCRIPTION

ARDEX WPM 265 (Sheltercoat Water Based Primer) is a red pigmented, acrylic primer system which creates a positive bond between the substrate and most water based coatings. Designed principally for internal use, ARDEX WPM 265 can also be used for external applications.

TYPICAL APPLICATIONS

- New and old concrete
- Timber
- Compressed fibreboards
- Primer for acrylic coatings

APPLICATION REQUIREMENTS

Substrate Preparation

The surface to be coated should be dry, clean, sound and free from oil, grease and flaking paint. New concrete should be left a minimum of 28 days and new render a minimum of 7 days before application commences. All cracks or holes exceeding 2mm are to be repaired before application commences.

Application

Apply with brush, long nap roller or conventional spray. Ensure that the coating is applied evenly at the recommended coverage rates. Allow a drying time of at least one hour.

LIMITATIONS

Do not apply ARDEX WPM 265 if the temperature is below 10°C or above 35°C.

Primed surfaces should preferably be overcoated within the same day of application to avoid intercoat contamination.

COVERAGE

Approximately 6 m²/litre. Coverage rate may vary depending on the porosity of the surface.

PACKAGING

20L plastic pails.

CLEAN UP

Clean all equipment in fresh water immediately after use.

SHELF LIFE

One year in unopened containers stored at 20°C.

STORAGE

ARDEX WPM 265 must be stored above 6°C.

SAFETY PRECAUTIONS

ARDEX WPM 265 is non-toxic goods. Avoid contact with skin and inhalation of the vapour. Wear protective eye/face protection and gloves when handling. Provide adequate ventilation. Wash off splashes with clean water. If irritation persists, seek medical advice.

ADDITIONAL INFORMATION IS LISTED IN THE MATERIAL SAFETY DATA SHEET.

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program.

Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations.

The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

ARDEX Australia Pty Ltd

New South Wales	Ph (02) 9851 9100	Fax (02) 9838 7970
Queensland	Ph (07) 3817 6000	Fax (07) 3881 3188
Victoria/Tasmania	Ph (03) 9308 9255	Fax (03) 9308 9332
South Australia	Ph (08) 8268 2511	Fax (08) 8345 3207
Western Australia	Ph (08) 9256 8600	Fax (08) 9455 1227

ARDEX New Zealand Ltd

Auckland	Ph (09) 5800 005	Fax (09) 5799 963
Wellington	Ph (04) 5685 949	Fax (04) 5686 376
Christchurch	Ph (03) 3843 029	Fax (03) 3849 779

Technical Services Toll Free: 1800 224 070

Date: July 2007