

Heavy Grade Hydroseal

A BITUMEN BASED WATERPROOFING SEALANT

Key Benefits Summary

- Low Cost
- Will not slump at temperatures up to 70°C
- Will not contaminate drinking water

PRODUCT INFORMATION

DESCRIPTION

Heavy Grade Hydroseal is a thick, inert fibre reinforced solvent cut bituminous mastic. It is easy to use and adheres to all dry, clean surfaces. Heavy Grade Hydroseal is alkali and acid resistant, and when dry it will not contaminate drinking water. Specially designed to be trowel applied to any surface. It forms a tough skin quickly then dries slowly beneath the surface.

USAGE/PURPOSE

Heavy Grade Hydroseal is specially formulated for waterproofing and sealing cracks, laps or joints and fixings on new or old structures of metal, concrete and timber.

It is Ideally suited for:

Domestic, Industrial and Commercial Buildings:

- Roof sheetings.
- Flashings and Cappings.
- Box and valley gutters.
- Downpipes.
- Under screws.
- Washers.

Rural Applications:

- Sheds and other buildings.
- Water tanks.
- Troughs.

Marine Work:

- Sealing against water, Drafts and Fumes.
- Bedding in deck timber.
- Sealing fixed windows.

PACK SIZE

- 550gm Pail
- 1kg Pail
- 4kg Pail

PRODUCT CODE

- 130120
- 130107
- 130108

COLOUR

Black

TECHNICAL INFORMATION

CHARACTERISTICS

- Flashpoint: 34°C (min)
- Coverage: 1kg will fill a joint approx. 25mm x 5mm x 8M long
- Net Weight: Approx 1 litre/1.1kg

USAGE GUIDELINES

SURFACE PREPARATION

- Apply to clean, dry surfaces, free from dirt, wax, grease, oily residue and all loose paint, rust and other material.
- No primer required.
- Can be applied to damp metallic surfaces.

APPLICATION

- Use direct from container applying thickly with a trowel, knife or caulking gun. For large holes use a glass mesh or strong cloth to reinforce.
- First apply a liberal coating of Heavy Grade Hydroseal into and around the hole or crack, cut mesh or cloth to fit across the hole and to overlap at least 6". Embed this around the hole.
- Then apply a further coating of Heavy Grade Hydroseal to cover the mesh entirely.
- To provide UV protection on exterior applications, after 14 days (minimum) drying,
- Heavy Grade Hydroseal can be painted with a water based paint such as Tremco Tennis Court Paint or a bituminous silver paint such as Tremco Alumicool.

CLEAN UP

Thoroughly clean, tools and equipment with mineral turps and rinse under water. Hands can be cleaned using appropriate hand cleanser.

STORAGE

Store in sealed containers under cover at normal temperatures for 12 months. Containers must be kept sealed at all times when the material is not being used.

HEALTH & SAFETY PRECAUTIONS

The Material Safety Data Sheet (MSDS) must be read and understood prior to use. When applying in confined spaces, ensure adequate ventilation. Avoid contact with skin and eyes.

TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.