

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name SEAL N FLEX 1 GREY

Product Code(s)

30800510
30800510; 30803243; 30804603; 30840034

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesives and/or sealants

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

Acute toxicity - Inhalation (Vapors)	Category 4 - (H332)
Respiratory sensitization	Category 1 - (H334)
Skin sensitization	Category 1 - (H317)

Label elements

Exclamation mark
Health hazard

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019



Signal word

Danger

Hazard statements

H317 - May cause an allergic skin reaction

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

In case of inadequate ventilation wear respiratory protection

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Causes mild skin irritation

Toxic to aquatic life

Product dust may be irritating to eyes, skin and respiratory system

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S6

Label requirements in accordance with SUSMP

POISON

KEEP OUT OF REACH OF CHILDREN

READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No.	Weight-%
Xylenes (o-, m-, p- isomers)	1330-20-7	0 - 10%
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0 - 10%
Benzene, 1,3-diisocyanatomethyl-	26471-62-5	0 - 10%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

Poisons Information Center, New Zealand: 0800 764 766

FIRST AID

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical advice/attention.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	May produce an allergic reaction. Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing dust/fume/gas/mist/vapors/spray.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Hives. Difficulty in breathing.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

Section 5: Firefighting measures

Suitable extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
-------------------------------------	---

Unsuitable extinguishing media	No information available.
---------------------------------------	---------------------------

Specific hazards arising from the chemical

Specific hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by inhalation and skin contact.
---	--

Hazardous Combustion Products	Carbon oxides.
--------------------------------------	----------------

Special protective actions for fire-fighters

Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away
-----------------------------	---

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

from and upwind of spill/leak. Avoid generation of dust. Do not breathe dust.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid generation of dust.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Avoid breathing dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Incompatible materials None known based on information supplied.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	Australia
Xylenes (o-, m-, p- isomers) 1330-20-7	80 ppm TWA 350 mg/m ³ TWA 150 ppm STEL 655 mg/m ³ STEL

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers
Eyewash stations

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear suitable protective clothing.
Hand protection	Wear suitable gloves.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Environmental exposure controls	No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Solid
Appearance	Paste
Color	Gray
Odor	Characteristic
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash Point	No data available	
Evaporation Rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor Pressure	1	
Vapor Density	No data available	
Relative Density	No data available	
Water Solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Kinematic Viscosity	No data available	
Dynamic Viscosity	No data available	
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>Other information</u>		
Solid content (%)	No information available	
VOC (volatile organic compound)	64 g/L	
Density	1.6 g/cm ³	

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

Stability Stable under normal conditions.

Explosion Data
Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization may occur.

Conditions to avoid

Conditions to avoid Excessive heat.

Incompatible materials

Incompatible materials None known based on information supplied.

Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen cyanide. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Section 11: TOXICOLOGICAL INFORMATION

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause sensitization in susceptible persons. (based on components). Harmful by inhalation.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitization by skin contact. Causes mild skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional affects as listed under "Inhalation".

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 28,442.00 mg/kg
ATEmix (dermal) 7,649.00 mg/kg mg/l
ATEmix (inhalation-dust/mist) 29.22 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= >47635 mg/L (Rat) 4 h = >5000 ppm (Rat) 4 h
Benzenesulfonyl isocyanate, 4-methyl-	= 2234 mg/kg (Rat)	-	> 640 ppm (Rat) 1 h

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

Benzene, 1,3-diisocyanatomethyl-	= 3060 mg/kg (Rat)	= 10000 mg/kg (Rabbit)	= 0.107 mg/L (Rat) 4 h (Vapour)
-------------------------------------	----------------------	--------------------------	--------------------------------------

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	May cause sensitization by inhalation. May cause sensitization by skin contact.
Germ cell mutagenicity	No information available.
Carcinogenicity	.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia
Benzene, 1,3-diisocyanatomethyl- 26471-62-5	Carc. 2

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (water flea)

Persistence and degradability

Persistence and degradability	No information available.
--------------------------------------	---------------------------

Bioaccumulative potential

Bioaccumulative potential	There is no data for this product.
----------------------------------	------------------------------------

Component Information

Chemical name	Partition coefficient
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	0.6

Mobility

Mobility in soil	No information available.
-------------------------	---------------------------

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

Mobility No information available.

Other Adverse Effects

Other Adverse Effects No information available.

Endocrine Disruptor Information

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S6

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Named hazardous chemicals

Chemical name	Threshold quantity (T)
Benzene, 1,3-diisocyanatomethyl- 26471-62-5	200 tonne TQ

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Xylenes (o-, m-, p- isomers) 1330-20-7	10 tonne/yr Threshold category 1 including individual or mixed isomers 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

	400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Benzene, 1,3-diisocyanatomethyl- 26471-62-5	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AICS	Listed
NZIoC	Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Not Listed

Legend:

- AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision Date 20-Feb-2019

Revision note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Safety Data Sheet

SEAL N FLEX 1 GREY
Revision Number 1.01

Revision Date 20-Feb-2019
Supersedes Date: 19-Feb-2019

End of Safety Data Sheet