



Total Waterproofing Supplies Pty Ltd

Butyl sealing tape with polypropylene fleece

Technical Data Sheet

Description

It is a single-side butyl tape, self-adhesive, non- shrinking butyl sealing tape laminated on one side with a nonwoven fabric.

Material and Structure



Siliconised Release Liner

Premium Butyl Rubber Adhesive

Non-Woven Polypropylene fleece

Key features and applications

- *Permanent bond
- *Non-shrinking
- *Odourless
- *Easy to install
- *Sound-absorbing
- *Mechanical reinforcement
- * Immediate performance
- *Environment-friendly
- *Free from solvents and bitumen
- *Water resistant and waterproof
- *Resistant to ageing, weathering

- Easily applied, instant adhesion to most substrates & long life durability with no leaching.
- Especially designed for waterproofing in wet rooms, bathrooms.
- Excellent as a waterproofing airtight tape used in building & construction applications.
- Compatible with most tile adhesives & texture coating systems.
- Used as a watertight, airtight joint seal / flashing tape in house cavities.

Main technical details

Items	Results
Compound	Butyl rubber adhesive
Lamination	Polypropylene fleece
Density	approx. 1.5 g/cm ³
Low temperature flexibility	no-crackle on surface @ -40±2°C
Heat resistance	No flowing & no crack & no deformation @ 95°C±5 for 2h
Solids	100%
Application Temperature	+5 °C to +40 °C recommended
Service Temperature	-40°C to +100°C