

# Kemcote Gloss

## Packaging



## Mixing



## Application



## Uses



## Substrates

**Walls:**  
Concrete,  
brick, block  
**Floors:**  
Slate &  
Concrete

A clear, gloss, 'wet look' coating for porous surfaces and slate

## Description

A clear, gloss, 'wet look', non-yellowing, hard-wearing, solvent-based coating that highlights colour, seals and protects porous, internal surfaces and slate.

**Not to be used on terracotta, pavers, around swimming pools and spas or areas subject to continuous moisture.**

## Uses

Use on architectural features and porous flooring stone. Seals and protects, slate, brick and concrete surfaces.

## Features

- Long lasting – tests have shown years of dependable protection
- Seals surface from moisture and protects surface from atmospheric chemical attack
- Will not darken or yellow with age
- May be recoated at any time

## Coverage (Approximate)

8-10 m<sup>2</sup>/litre/coat.

## Performance Data

### Surface Water Absorption

BS1881 Parts Section 6

Short term (1 hour) 0.0095 (mL/m<sup>2</sup>/sec)

Long term (24 hours) 0.0103 (mL/m<sup>2</sup>/sec)

Reduces moisture absorption by 85%

### Chemical Resistance

Moderate resistance to acids and alkali

## Specification

The sealer shall be a solvent acrylic sealer and reduce water absorption by 85% such as **Kemcote Gloss** manufactured by **Construction Chemicals** and shall be applied in accordance with the application instructions.

## Surface Preparation

Surface to be coated must be firm, clean, dry and free of oil, grease, efflorescence, contaminants and other coatings. Do not apply over paint, loose or crumbly surfaces or to very dense impervious surfaces such as marble tiles or polished stone. New concrete should have cured for 28 days and allow damp substrates up to 3 days to dry thoroughly depending on temperature. New floors are cleaned by scrubbing with warm water mixed with a mild household detergent, washed with clean water and allowed to dry thoroughly. If the substrate is not completely dry or is in prolonged damp situations the coating will discolour.

**To check the suitability of a sealer apply a test area before commencing.**

## Application

Apply in temperatures above 5°C. Apply with a paint brush or lambswool applicator. Apply two coats, the first to saturate the surface. Avoid applying excessive thicknesses or in puddles. Allow 2-3 hours between coats. Apply the second coat evenly without leaving streaks or brush marks. Allow surface to dry before putting into use. When recoating after areas have been in use for some time, scrub area with detergent to remove dirt and grease and wash with clean water and let dry for 2-3 days before recoating.

## Storage

Keep in a cool dry place away from open fires, heater and stoves etc.

## Precautions

**Kemcote Gloss** will be marked or scratched in highly abrasive traffic areas. Protect the surface from scratching by using felt pads on the base of furniture. **Do not use in situations of rising damp or where continuous moisture is present as the coating will whiten.**

## Solvent

 Xylene or similar.

## Safety Instructions

Contains flammable solvents in the liquid state. Do not smoke during application or apply in the presence of naked flames, electrical equipment or sparks. Ensure adequate ventilation during application and drying period. Avoid contact with skin or eyes, breathing vapour or mist spray. Keep out of children's reach.

## First Aid

If swallowed do not induce vomiting. Give a glass of water and contact a doctor or Poisons Information Centre.

## Shelf Life

2 years

*Sealer Disclaimer: This product is used under conditions that are beyond our control, the manufacturer will not be responsible for the results obtained. Liability is restricted to the replacement of any material proved faulty and the manufacturer is not responsible for loss or damage arising from incorrect usage. Determining the suitability of the product for any intended use shall be the sole responsibility of the user.*