

# Enviro Prime SB

## Universal Fast Drying Primer



### DESCRIPTION

Enviro Prime SB is a universal solvent-based primer. It provides excellent adhesion for most of Envirosystems range of products including Enviro 700X and 200P Ultra.

### FEATURES

- Simple to use – 1 part
- Versatile / universal
- Suitable for a wide range of substrates
- Fast drying

### TYPICAL USES

Enviro Prime SB is suitable for use with the following range of Envirosystems products:

- Enviro Clad
- Enviro 700X
- Enviro 700X-SL
- Enviro 200P Ultra

### RECOMMENDED SUBSTRATES

Enviro Prime SB can be used across a variety of substrates including:

- Render
- Concrete
- Block work
- F.C. sheeting (untreated)
- Bricks
- Most existing coatings (subject to trial)
- Non-ferrous abraded metal (e.g. aluminium angle)
- PVC pipes and angles (abraded)
- Timber

### SUBSTRATE PREPARATION

The surface must be clean, and free from all loose particles, including dust, laitance, grease, coatings, curing compounds or any other foreign matter.

Where boards are used, these are to be fixed according to the manufacturer's instructions and will need to be fit for purpose. Apply suitable and approved polyurethane joint caulking material such as Enviro Flex Pro or Flex FC and allow to cure before application of Enviro Prime SB to all joints, internal corners, and substrate cracks.

For further information on substrate preparation or for project specific advice, please consult Envirosystems.

[customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

### MIXING

Enviro Prime SB should be thoroughly mixed using mechanical mixing at low speed prior to application.

### APPLICATION

Enviro Prime SB can be applied using brush or roller. Apply one coat of Enviro Prime SB to the prepared substrate. Allow to dry before proceeding with the application of the selected membrane or coating.

For porous substrates, a second coat of Prime SB can be considered to ensure that the treated surface is sufficiently sealed.

For further information regarding application of Enviro Prime SB or for project specific advice please consult Envirosystems.

[customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

### COVERAGE

The consumption of Enviro Prime SB will depend upon substrate condition and type.

**Coverage Rate:** 5m<sup>2</sup> – 8m<sup>2</sup> per litre.

### CURE

Enviro Prime SB generally can be overcoated after 1 hour depending on the weather.

### PACKAGING & COLOURS

Enviro Prime SB is clear and supplied in 1, 4 and 15 L drums.



## CLEANING

Enviro Prime SB should be removed from all tools and equipment, prior to hardening with Enviro Thinners No.1 or Enviro Thinners No. 7. Alternatively, a universal cleaning solvent can be used. Cured material can only be mechanically removed.

## SHELF LIFE

Enviro Prime SB can be stored in its original tightly sealed container for at least 12 months if kept stored in a dry place out of direct sunlight and between 0°C and 35 °C. Once opened and resealed for later use, the shelf life could vary depending on storage conditions. Always check product quality before using after prolonged periods of storage. If unsure, please contact EnviroSystems for advice.

## HEALTH & SAFETY ADVICE

Enviro Prime SB contents are flammable. Keep away from naked flame. In the event of fire extinguish with foam or CO. Always provide adequate ventilation and wear appropriate personal protection equipment (PPE) during use. Avoid breathing vapours. Avoid contact with skin. If swallowed, DO NOT induce vomiting, give glass of water and seek immediate medical advice. If contact with skin, wash off splashes of material with clean water and soap. If irritation occurs seek immediate medical advice. Refer to the Safety Data Sheet for full safety and handling procedures.

**NOTE:** Safety Data Sheets are available upon request by emailing [customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

## We're here to help you!

It is a good idea to keep a journal of your waterproofing job, whether big or small.

- Take pictures at all stages of your work, including preparation
- Record the quantity and description of products used with corresponding batch numbers
- Record dates and times of when you applied products, from start to finish

Please do not hesitate to contact us for any questions you may have.

EnviroSystems Technologies Pty Ltd

**Address** 295 Princes Highway, St Peters NSW 2044  
Sydney, Australia  
**Phone** +61 2 8595 8699  
**Fax** +61 2 8595 8660  
**Email** [customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)  
**Web** [www.envirosystems.com.au](http://www.envirosystems.com.au)

**DATE** August 2020



### STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use. Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by EnviroSystems Technologies either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not EnviroSystems Technologies are responsible for carrying out procedures appropriate to a specific application.