



JB25 & JB50

FLEXIBLE BOND BREAKER

Product Overview

TWS JB25 & JB50 Joint Band is designed to ensure effective detailing over all kinds of joints & junctions. Our joint band features a seamless butynol rubber strip that follows along the joint forming a long term, waterproof & rupture resistant seal. JB25 & JB50 acts as a high-performance bond breaker, accommodating movement in multiple directions and allowing high elongation in critical areas

Product Features

- High strength & excellent tear resistance
- Faster application compared to traditional bond breaking methods
- Excellent elastic recovery when exposed to movement
- Enables a seamless elastic seal over wall/floor junctions, control joints, movement & expansion joints
- Long term protection at critical movement zones
- Compatible with all water-based TWS membranes

General Application Details

- Apply a liberal coat of the TWS water-based membrane to the substrate, ensuring enough membrane is applied to cover the back of the entire joint band along the joint
- While the membrane is still wet, embed the joint band into the membrane ensuring the fabric edges have been fully wetted in
- Using a flat spatula or brush, ensure creases and air bubbles in fabric edges are pushed out
- Where TWS – JB90 or JB270 corner profiles are used TWS – Joint Band is to be overlapped 50mm and adhered to the corner profile with membrane for a continuous elastic seal

Important Notes

- Not compatible with Solvent-Based material, only to be used in conjunction with Water-Based membranes
- It is recommended that prior to application, the adhesion of products to be used is tested over a typical area of the prepared surface to ensure adequate adhesion, if membrane does not have proper adhesion to the surface, corner profiles should not be installed

Packaging

- JB25 – 25m x 120mm Roll
- JB50 – 50m x 120mm Roll

Contact Details

TOTAL WATERPROOFING SUPPLIES CORPORATE PTY LTD

Telephone: +61 (2) 4940-3000

Email: sales@totalwaterproofingsupplies.com.au

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Total Waterproofing Supplies does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.