



# JB90 & JB270

## FLEXIBLE BOND BREAKER

### Product Overview

TWS JB90 & JB270 prefabricated corners are designed to ensure effective detailing at critical 90° and 270° corner intersections. Our prefabricated corners feature a seamless butynol rubber strip that follows along the wall/floor junction forming a long term, waterproof & rupture resistant seal.

### Product Features

- High strength & excellent tear resistance
- Faster application compared to traditional bond breaking methods
- Excellent elastic recovery when exposed to movement
- Enables a seamless elastic seal at joint intersections
- Eliminates lapping & bonding of fabrics at critical corner areas
- Compatible with all water-based TWS membranes

### General Application Details

- Apply a liberal coat of the TWS water-based membrane to the substrate, ensuring enough membrane is applied to cover the back of the entire corner profile
- While the membrane is still wet, embed the corner profile into the membrane ensuring the fabric edges have been fully wetted in
- Using a flat spatula or brush, ensure creases and air bubbles in fabric edges are pushed out
- TWS – JB50 Joint Band is to be overlapped 50mm and adhered to the corner profile with membrane for a continuous elastic seal

### Important Notes

- Not compatible with Solvent-Based material, only to be used in conjunction with Water-Based membranes
- It is recommended that prior to application, the adhesion of products to be used is tested over a typical area of the prepared surface to ensure adequate adhesion, if membrane does not have proper adhesion to the surface, corner profiles should not be installed

### Packaging

- Individual Corner Profile
- Box of 10

### Contact Details

TOTAL WATERPROOFING SUPPLIES CORPORATE PTY LTD

Telephone: +61 (2) 4940-3000

Email: [sales@totalwaterproofingsupplies.com.au](mailto:sales@totalwaterproofingsupplies.com.au)

#### Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Total Waterproofing Supplies does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.